

CIRCULAR LETTER	No. 314-18-1677c	dated 06.12.2021		
Re:				
amendments to the Rules ND No. 2-020101-138-E	for the Classification	and Construction of	Sea-Going Ships, 2021,	
Item(s) of supervision:				
ship under construction				
Entry-into-force date: 01.01.2022				
Cancels / amends / adds Circu	ılar Letter No.	-	dated -	
Number of pages: 1+2				
Appendices:				
Appendix 1: information on am	endments introduced by	y the Circular Letter		
Appendix 2: text of amendmer	its to Part III "Equipmen	t, Arrangements and Outf	fit"	
Director General	Konstantin	G. Palnikov		
Text of CL:				
We hereby inform that the R amended as specified in the A			Sea-Going Ships shall be	
It is necessary to do the follow	ing:			
1.Bring the content of the Circ persons in the area of the R			terested organizations and	
2. Apply the provisions of the C ships contracted for constru- keels of which are laid or wh	ction or conversion on o	r after 01.01.2022, in the	absence of a contract, the	
List of the amended and/or int	roduced paras/chapters/	sections:		
Part III: para 8.5.4.3				

Person in charge:	Sergey O. Rud	314
"Thosis" System No	21 225/52	

+7(812) 312-85-72

Thesis" System No. 21-285458

Information on amendments introduced by the Circular Letter (for inclusion in the Revision History to the RS Publication)

Nos.	Amended paras/chapters/ sections	Information on amendments	Number and date of the Circular Letter	Entry-into-force date
1	Para 8.5.4.3	Requirement for the angle of slope of fishing vessels has been specified	314-18-1677c of 06.12.2021	01.01.2022

RULES FOR THE CLASSIFICATION AND CONSTRUCTION OF SEA-GOING SHIPS, 2021

ND No. 2-020101-138-E

PART III. EQUIPMENT, ARRANGEMENTS AND OUTFIT

8 ARRANGEMENT AND EQUIPMENT OF SHIP'S SPACES. OTHER ARRANGEMENTS AND EQUIPMENT

Para 8.5.4.3 is replaced by the following text:

"8.5.4.3 Stairways used as means of escape on cargo ships shall be at least 700 mm wide and shall be fitted with a handrail on either side. Stairways with a width of 1800 mm and more shall be fitted with handrails on each side. In cargo ships of less than 500 gross tonnage the width of stairways may be 600 mm. Angle of slope of ladders shall be usually 45° but not greater than 50°, in the machinery and in small spaces — not greater than 60°. In ships of less than 500 gross tonnage and fishing vessels in case of insufficient space at egress from the stairway, the stairways may be installed with the angle of slope of ladders of 55° in accommodation and service spaces, with 60° — on decks. The size of doors providing an access to any stairway shall be of the same size as the stairway.".